

MIROTONE

Leading the way in coating systems since 1938

MIROLAC NC 235 HOT SPRAY GLOSS

Chemwatch Material Safety Data Sheet
Issue Date: 29-Jan-2010
XC9477SC

Hazard Alert Code: HIGH

CHEMWATCH 5089-23
Version No:5
CD 2011/2 Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

MIROLAC NC 235 HOT SPRAY GLOSS

STATEMENT OF HAZARDOUS NATURE

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation.

OTHER NAMES N/A

PROPER SHIPPING NAME

PAINT

PRODUCT USE

■ The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.
Used according to manufacturer's directions.
Coating for furniture.

SUPPLIER

Company: Mirotone (NZ) Limited

Address:

32 Cryers Road

East Tamaki, Manukau 2163

P.O. Box 58149, Botany, Manukau 2013,

Telephone: 0800 FINISH (0800 34 64 74)

Telephone: 09 272 2562


Emergency Tel: **111 In Case of Fire or Spill**

Emergency Tel: **0800 POISON (0800 764 766)**

Fax: 0800 34 64 34

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



GHS Classification

Acute Toxicity Category 4

Chronic Aquatic Hazard Category 3

continued...

Chemwatch Material Safety Data Sheet

Issue Date: 29-Jan-2010

XC9477SC

CHEMWATCH 5089-23

Version No:5

CD 2011/2 Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

Eye Irritation Category 2A
 Flammable Liquid Category 2
 Reproductive Toxicity Category 2
 Skin Corrosion/Irritation Category 2
 STOT - RE Category 2
 STOT - SE Category 3



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by Chemwatch using GHS/HSNO criteria

3.1B	Highly flammable liquid and vapour.
6.1D	Harmful if swallowed.
6.3A	Causes skin irritation.
6.4A	Causes serious eye irritation.
6.8B	Suspected of damaging fertility or the unborn child.
6.9	May cause respiratory irritation.
6.9B	May cause damage to organs through prolonged or repeated exposure.
9.1D	Harmful to aquatic life
9.3C	Harmful to terrestrial vertebrates

PRECAUTIONARY STATEMENTS

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion- proof electrical/ventilating/lighting/ ... /equipment
P242	Use only non- sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well- ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.

Response

P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P330	Rinse mouth.
P337+P313	If eye irritation persists: Get medical advice/attention.

Storage

P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P403+P235	Store in a well- ventilated place. Keep cool.
P405	Store locked up.

Disposal

P501	Dispose of contents/container to ...
------	--------------------------------------

continued...

Chemwatch Material Safety Data Sheet
Issue Date: 29-Jan-2010
XC9477SC

Hazard Alert Code: HIGH

CHEMWATCH 5089-23
Version No:5
CD 2011/2 Page 3 of 10

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
toluene	108-88-3	30-60
solvents		30-60
resins		10-30
pigments		10-30
additives		0-10

Section 4 - FIRST AID MEASURES

NEW ZEALAND POISONS INFORMATION CENTRE 0800 POISON (0800 764 766)
NZ EMERGENCY SERVICES: 111

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

continued...

Chemwatch Material Safety Data Sheet
Issue Date: 29-Jan-2010
XC9477SC

Hazard Alert Code: HIGH

CHEMWATCH 5089-23
Version No:5
CD 2011/2 Page 4 of 10

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
 - May be violently or explosively reactive.
 - Wear breathing apparatus plus protective gloves.
 - Prevent, by any means available, spillage from entering drains or water course.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat, flame and/or oxidisers.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
- Combustion products include: carbon dioxide (CO₂), nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.
- Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
 - Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Contains low boiling substance:
Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.
- Check for bulging containers.
 - Vent periodically
 - Always release caps or seals slowly to ensure slow dissipation of vapours.
 - DO NOT allow clothing wet with material to stay in contact with skin.

continued...

Chemwatch Material Safety Data Sheet

Issue Date: 29-Jan-2010

XC9477SC

CHEMWATCH 5089-23

Version No:5

CD 2011/2 Page 5 of 10

Section 7 - HANDLING AND STORAGE

- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec).
- Avoid splash filling.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C).

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE CONTROLS**

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
New Zealand Workplace Exposure Standards (WES)	toluene (Toluene)	50	188						skin

PERSONAL PROTECTION**RESPIRATOR**

- Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

continued...

Chemwatch Material Safety Data Sheet

Issue Date: 29-Jan-2010

XC9477SC

CHEMWATCH 5089-23

Version No:5

CD 2011/2 Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Coloured flammable liquid with a characteristic odour; not miscible with water.

PHYSICAL PROPERTIES

Liquid.

State	Liquid	Molecular Weight	Not Available
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Partly Miscible
Flash Point (°C)	- 6.7	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.930- 1.08
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	55- 75 (VOC=630- 680 g/l)	Evaporation Rate	Not Available

Material	Value
TOLUENE:	
log Kow	2.1- 3

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
 - Considered an unlikely route of entry in commercial/industrial environments.
- The liquid may produce gastrointestinal discomfort and may be harmful if swallowed.

EYE

- Evidence exists, or practical experience predicts, that the material may cause severe eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.
- Eye contact may cause significant inflammation with pain.
- The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis.
- Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.

SKIN

- Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

INHALED

- The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models).
- Nevertheless inhalation, of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

CHRONIC HEALTH EFFECTS

- Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. There is sufficient evidence to provide a strong presumption that human exposure to the material may result in developmental toxicity, generally on the basis of:
- clear results in appropriate animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects.
- Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.
- On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.
- Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.
- Chronic toluene habituation occurs following intentional abuse (glue sniffing) or from occupational exposure. Ataxia, incoordination and tremors of the hands and feet (as a consequence of diffuse cerebral atrophy), headache, abnormal speech, transient memory loss, convulsions, coma, drowsiness, reduced colour perception, frank blindness, nystagmus (rapid, involuntary eye-movements), hearing loss leading to deafness and mild dementia have all been associated with chronic abuse.

TOXICITY AND IRRITATION

- The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
- The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.
- For toluene:
- Acute Toxicity
- Humans exposed to intermediate to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis, and death. Similar effects are observed in short-term animal studies.</>.

CARCINOGEN

Toluene

International Agency for Research on Cancer
 (IARC) - Agents Reviewed by the IARC
 Monographs

Group

3

continued...

Chemwatch Material Safety Data Sheet
Issue Date: 29-Jan-2010
XC9477SC

Hazard Alert Code: HIGH

CHEMWATCH 5089-23
Version No:5
CD 2011/2 Page 8 of 10

Section 11 - TOXICOLOGICAL INFORMATION

REPROTOXIN

toluene	ILO Chemicals in the electronics industry that have toxic effects on reproduction	Reduced fertility or sterility
---------	---	--------------------------------

SKIN

toluene	New Zealand Workplace Exposure Standards (WES) - Skin	Notes	skin
---------	---	-------	------

Section 12 - ECOLOGICAL INFORMATION

toluene 96 hr LC50 (8.11) mg/L Coho salmon,silver salmon Fish Source: Experimental

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
MIROLAC NC 235 HOT SPRAY GLOSS	No Data	No Data		
toluene	Available LOW	Available MED	LOW	MED

Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.
- A Hierarchy of Controls seems to be common - the user should investigate:
- Reduction.
 - DO NOT allow wash water from cleaning or process equipment to enter drains.
 - It may be necessary to collect all wash water for treatment before disposal.
 - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
 - Where in doubt contact the responsible authority.
 - Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
 - Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
- Insure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.*

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID

HAZCHEM:

•3Y

Land Transport UNDG:

continued...

Chemwatch Material Safety Data Sheet

Issue Date: 29-Jan-2010

XC9477SC

CHEMWATCH 5089-23

Version No:5

CD 2011/2 Page 9 of 10

Section 14 - TRANSPORTATION INFORMATION

Class or division:	3	Subsidiary risk:	None
UN No.:	1263	UN packing group:	II
Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)			

Air Transport IATA:

UN/ID Number:	1263	Packing Group:	II
Special provisions:	A3		
Cargo Only			
Packing Instructions:	364	Maximum Qty/Pack:	60 L
Passenger and Cargo		Passenger and Cargo	
Packing Instructions:	Y341	Maximum Qty/Pack:	5 L
Passenger and Cargo Limited Quantity		Passenger and Cargo Limited Quantity	
Packing Instructions:	353	Maximum Qty/Pack:	1 L

Shipping name: PAINT

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	II
EMS Number:	F-E,S-E	Special provisions:	163
Limited Quantities:	5 L		
Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer bas			

Section 15 - REGULATORY INFORMATION

ERMA Approval number

This substance is to be managed in accordance with the classification and controls specified in the Hazardous Substances Transfer Notice, 2004, (see table below). This substance may alternatively be managed under the conditions imposed by an applicable Group Standard.

HSR No.	HSR Name
HSR002495	Additives, Process Chemicals and Raw Materials (Flammable) Group Standard 2006
HSR002528	Cleaning Products (Flammable) Group Standard 2006
HSR002548	Corrosion Inhibitors (Flammable) Group Standard 2006
HSR002552	Cosmetic Products Group Standard 2006
HSR002556	Dental Products (Flammable) Group Standard 2006
HSR002563	Embalming Products (Flammable) Group Standard 2006
HSR002576	Food Additives and Fragrance Materials (Flammable) Group Standard 2006
HSR002583	Fuel Additives (Flammable) Group Standard 2006
HSR002599	Leather and Textile Products (Flammable) Group Standard 2006
HSR002611	Metal Industry Products (Flammable) Group Standard 2006
HSR002621	N.O.S. (Flammable) Group Standard 2006
HSR002637	Photographic Chemicals (Flammable) Group Standard 2006
HSR002641	Polymers (Flammable) Group Standard 2006
HSR002650	Solvents (Flammable) Group Standard 2006
HSR002662	Surface Coatings and Colourants (Flammable) Group Standard 2006
HSR100425	Pharmaceutical Active Ingredients Group Standard 2010
HSR002603	Lubricants (Flammable) Group Standard 2006

REGULATIONS

Regulations for ingredients

toluene (CAS: 108-88-3) is found on the following regulatory lists:

"IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Fragrance Association (IFRA) Standards Prohibited", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data", "New Zealand Hazardous Substances and New Organisms (HSNO) Act -

continued...

Chemwatch Material Safety Data Sheet

Issue Date: 29-Jan-2010

XC9477SC

Hazard Alert Code: HIGH**CHEMWATCH 5089-23****Version No:5****CD 2011/2 Page 10 of 10****Section 15 - REGULATORY INFORMATION**

Dangerous Goods", "New Zealand Hazardous Substances and New Organisms (HSNO) Act - Pesticides", "New Zealand Inventory of Chemicals (NZIoC)", "New Zealand Workplace Exposure Standards (WES)", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

distillates, petroleum, light, hydrotreated (CAS: 64742-47-8) is found on the following regulatory lists;

"International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "New Zealand Inventory of Chemicals (NZIoC)"

No data for MIROLAC NC 235 HOT SPRAY GLOSS (CW: 5089-23)

Specific advice on controls required for materials used in New Zealand can be found at
<http://www.ermanz.govt.nz/search/registers.html>

Section 16 - OTHER INFORMATION

NEW ZEALAND POISONS INFORMATION CENTRE

0800 POISON (0800 764 766)

NZ EMERGENCY SERVICES: 111

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 29-Jan-2010