



## MIROBILD AC 3722

Mirotone (NZ) Ltd

Chemwatch: 5136-74

Version No: 7.1.1.1

Safety Data Sheet according to HSNO Regulations

Chemwatch Hazard Alert Code: 3

Issue Date: 01/05/2015

Print Date: 05/05/2016

Initial Date: Not Available

L.GHS.NZL.EN

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | MIROBILD AC 3722   |
| Synonyms                      | 3722-A-, Product Code: 3722  |
| Proper shipping name          | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Other means of identification | Not Available  |

#### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Use according to manufacturer's directions.<br>Coating for furniture. |
|--------------------------|---|

#### Details of the supplier of the safety data sheet

|                         |                            |
|-------------------------|----------------------------|
| Registered company name | Mirotone (NZ) Ltd          |
| Address                 | 32 Cryers Road New Zealand |
| Telephone               | 0800 FINISH (0800 346 474) |
| Fax                     | 0800 346 434               |
| Website                 | mirotone.com               |
| Email                   | information@mirotone.co.nz |

#### Emergency telephone number

|                                   |               |
|-----------------------------------|---------------|
| Association / Organisation        | Not Available |
| Emergency telephone numbers       | 111           |
| Other emergency telephone numbers | Not Available |

#### CHEMWATCH EMERGENCY RESPONSE

| Primary Number | Alternative Number 1 | Alternative Number 2 |
|----------------|----------------------|----------------------|
| +800 2436 2255 | +612 9186 1132       | Not Available        |

Once connected and if the message is not in your preferred language then please dial 01

### SECTION 2 HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

**Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation.  
Classified as Dangerous Goods for transport purposes.**

#### CHEMWATCH HAZARD RATINGS

|              | Min | Max |
|--------------|-----|-----|
| Flammability | 3   | 3   |
| Toxicity     | 2   | 2   |
| Body Contact | 3   | 3   |
| Reactivity   | 1   | 1   |
| Chronic      | 2   | 2   |

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

|                               |   |
|-------------------------------|---|
| Classification <sup>[1]</sup> | Flammable Liquid Category 2, Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity - single exposure Category 3 (narcotic effects), Acute Aquatic Hazard Category 2 |
|-------------------------------|---|

Continued...

## MIROBILD AC 3722

**Legend:** 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Determined by Chemwatch  
using GHS/HSNO criteria

3.1B, 6.1D (dermal), 6.1D (inhalation), 6.1D (oral), 6.3A, 6.5B (contact), 6.9 (narcotic), 6.9 (respiratory), 8.3A, 9.1D

## Label elements

### GHS label elements



### SIGNAL WORD

**DANGER**

**Hazard statement(s)**

|             |                                      |
|-------------|--------------------------------------|
| <b>H225</b> | Highly flammable liquid and vapour.  |
| <b>H302</b> | Harmful if swallowed.                |
| <b>H312</b> | Harmful in contact with skin.        |
| <b>H332</b> | Harmful if inhaled.                  |
| <b>H315</b> | Causes skin irritation.              |
| <b>H318</b> | Causes serious eye damage.           |
| <b>H317</b> | May cause an allergic skin reaction. |
| <b>H335</b> | May cause respiratory irritation.    |
| <b>H336</b> | May cause drowsiness or dizziness.   |
| <b>H401</b> | Toxic to aquatic life                |

**Precautionary statement(s) Prevention**

|             |   |
|-------------|---|
| <b>P210</b> | Keep away from heat/sparks/open flames/hot surfaces. - No smoking.                |
| <b>P271</b> | Use only outdoors or in a well-ventilated area.                                   |
| <b>P280</b> | Wear protective gloves/protective clothing/eye protection/face protection.        |
| <b>P240</b> | Ground/bond container and receiving equipment.                                    |
| <b>P241</b> | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. |
| <b>P242</b> | Use only non-sparking tools.  |
| <b>P243</b> | Take precautionary measures against static discharge.                             |
| <b>P261</b> | Avoid breathing mist/vapours/spray.   |
| <b>P270</b> | Do not eat, drink or smoke when using this product.                               |
| <b>P273</b> | Avoid release to the environment.   |
| <b>P272</b> | Contaminated work clothing should not be allowed out of the workplace.            |

### Precautionary statement(s) Response

|                       |  |
|-----------------------|--|
| <b>P305+P351+P338</b> | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| <b>P310</b>           | Immediately call a POISON CENTER or doctor/physician.  |
| <b>P362</b>           | Take off contaminated clothing and wash before reuse.  |
| <b>P363</b>           | Wash contaminated clothing before reuse.   |
| <b>P370+P378</b>      | In case of fire: Use alcohol resistant foam or normal protein foam for extinction.   |
| <b>P302+P352</b>      | IF ON SKIN: Wash with plenty of soap and water.  |
| <b>P333+P313</b>      | If skin irritation or rash occurs: Get medical advice/attention.   |
| <b>P301+P312</b>      | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.   |
| <b>P303+P361+P353</b> | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.                       |
| <b>P304+P340</b>      | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                 |
| <b>P330</b>           | Rinse mouth.   |

**Precautionary statement(s) Storage**

|                  |  |
|------------------|--|
| <b>P403+P235</b> | Store in a well-ventilated place. Keep cool.                     |
| <b>P405</b>      | Store locked up.   |
| <b>P403+P233</b> | Store in a well-ventilated place. Keep container tightly closed. |

**Precautionary statement(s) Disposal**

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

## Substances

See section below for composition of Mixtures

Continued...

## MIROBILD AC 3722

## Mixtures

| CAS No        | %[weight] | Name   |
|---------------|-----------|--|
| 14807-96-6    | 30-60     | <u>talc</u>  |
| Not Available | 30-70     | resins   |
| 71-36-3       | 10-30     | <u>n-butanol</u>                                   |
| 9004-70-0     | 0-10      | <u>nitrocellulose</u>                              |
| 78-93-3       | 0-10      | <u>methyl ethyl ketone</u>                         |
| 141-78-6      | 0-10      | <u>ethyl acetate</u>                               |
| 123-86-4      | 0-10      | <u>n-butyl acetate</u>                             |
| 13463-67-7    | 0-10      | <u>titanium dioxide</u>                            |
| 61791-53-5    | 0-10      | <u>N-tallow(alkyl)-1,3-propanediamine dioleate</u> |
| 1330-20-7     | 10-30     | <u>xylene</u>                                      |
|               | balance   | Ingredients determined not to be hazardous         |

## SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

## Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul>   |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> </ul>      |

## Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

Treat symptomatically.

To treat poisoning by the higher aliphatic alcohols (up to C7):

- ▶ Gastric lavage with copious amounts of water.
- ▶ It may be beneficial to instill 60 ml of mineral oil into the stomach.
- ▶ Oxygen and artificial respiration as needed.
- ▶ Electrolyte balance: it may be useful to start 500 ml M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- ▶ To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- ▶ Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5]

## BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Anticipate and treat, where necessary, for seizures.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

## ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.

Continued...

## MIROBILD AC 3722

- ▶ If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

## EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Acidosis may respond to hyperventilation and bicarbonate therapy.
- ▶ Haemodialysis might be considered in patients with severe intoxication.
- ▶ Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Symptomatic and supportive therapy is advised in managing patients.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- ▶ Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- ▶ Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

## SECTION 5 FIREFIGHTING MEASURES

## Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

Do not use a water jet to fight fire.

## Special hazards arising from the substrate or mixture

## Fire Incompatibility

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

## Advice for firefighters

|                       |   |
|-----------------------|---|
| Fire Fighting         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ Fight fire from a safe distance, with adequate cover.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control the fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>Do not approach containers suspected to be hot.</b></li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul> |
| Fire/Explosion Hazard | <ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include; carbon dioxide (CO<sub>2</sub>) aldehydes nitrogen oxides (NO<sub>x</sub>) silicon dioxide (SiO<sub>2</sub>) other pyrolysis products typical of burning organic material</p>   |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

| Minor Spills       | <ul style="list-style-type: none"><li>▶ Remove all ignition sources.</li><li>▶ Clean up all spills immediately.</li><li>▶ Avoid breathing vapours and contact with skin and eyes.</li><li>▶ Control personal contact with the substance, by using protective equipment.</li><li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li><li>▶ Wipe up.</li><li>▶ Collect residues in a flammable waste container.</li></ul> |             |            |             |  |              |      |             |            |             |                    |  |  |  |  |
|--------------------|---|-------------|------------|-------------|--|--------------|------|-------------|------------|-------------|--------------------|--|--|--|--|
| Major Spills       | <p>Chemical Class: aromatic hydrocarbons</p> <p>For release onto land: recommended sorbents listed in order of priority.</p> <table><tr><th>SORBENT TYPE</th><th>RANK</th><th>APPLICATION</th><th>COLLECTION</th><th>LIMITATIONS</th></tr><tr><td colspan="5">LAND SPILL - SMALL</td></tr></table>  |             |            |             |  | SORBENT TYPE | RANK | APPLICATION | COLLECTION | LIMITATIONS | LAND SPILL - SMALL |  |  |  |  |
| SORBENT TYPE       | RANK  | APPLICATION | COLLECTION | LIMITATIONS |  |              |      |             |            |             |                    |  |  |  |  |
| LAND SPILL - SMALL |   |             |            |             |  |              |      |             |            |             |                    |  |  |  |  |

## MIROBILD AC 3722

|   |   |        |           |               |
|---|---|--------|-----------|---------------|
| Feathers - pillow                                   | 1 | throw  | pitchfork | DGC, RT       |
| cross-linked polymer - particulate                  | 2 | shovel | shovel    | R,W,SS        |
| cross-linked polymer- pillow                        | 2 | throw  | pitchfork | R, DGC, RT    |
| sorbent clay - particulate                          | 3 | shovel | shovel    | R, I, P,      |
| treated clay/ treated natural organic - particulate | 3 | shovel | shovel    | R, I          |
| wood fibre - pillow                                 | 4 | throw  | pitchfork | R, P, DGC, RT |

## LAND SPILL - MEDIUM

|   |   |        |            |                 |
|---|---|--------|------------|-----------------|
| cross-linked polymer -particulate                   | 1 | blower | skiploader | R, W, SS        |
| treated clay/ treated natural organic - particulate | 2 | blower | skiploader | R, I            |
| sorbent clay - particulate                          | 3 | blower | skiploader | R, I, P         |
| polypropylene - particulate                         | 3 | blower | skiploader | W, SS, DGC      |
| feathers - pillow                                   | 3 | throw  | skiploader | DGC, RT         |
| expanded mineral - particulate                      | 4 | blower | skiploader | R, I, W, P, DGC |

## Legend

DGC: Not effective where ground cover is dense

R: Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT: Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988

- ▶ Clear area of personnel and move upwind.
- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be violently or explosively reactive.
- ▶ Wear breathing apparatus plus protective gloves.
- ▶ Prevent, by any means available, spillage from entering drains or water course.
- ▶ Consider evacuation (or protect in place).
- ▶ No smoking, naked lights or ignition sources.
- ▶ Increase ventilation.
- ▶ Stop leak if safe to do so.
- ▶ Water spray or fog may be used to disperse /absorb vapour.
- ▶ Contain spill with sand, earth or vermiculite.
- ▶ Use only spark-free shovels and explosion proof equipment.
- ▶ Collect recoverable product into labelled containers for recycling.
- ▶ Absorb remaining product with sand, earth or vermiculite.
- ▶ Collect solid residues and seal in labelled drums for disposal.
- ▶ Wash area and prevent runoff into drains.
- ▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

## Precautions for safe handling

## Safe handling

- ▶ Containers, even those that have been emptied, may contain explosive vapours.
- ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- ▶ **DO NOT allow clothing wet with material to stay in contact with skin**
- ▶ Electrostatic discharge may be generated during pumping - this may result in fire.
- ▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- ▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec).
- ▶ Avoid splash filling.
- ▶ Do NOT use compressed air for filling discharging or handling operations.
- ▶ Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.
- ▶ Prevent concentration in hollows and sumps.
- ▶ **DO NOT enter confined spaces until atmosphere has been checked.**
- ▶ Avoid smoking, naked lights, heat or ignition sources.
- ▶ When handling, **DO NOT eat, drink or smoke.**
- ▶ Vapour may ignite on pumping or pouring due to static electricity.
- ▶ **DO NOT use plastic buckets.**
- ▶ Earth and secure metal containers when dispensing or pouring product.
- ▶ Use spark-free tools when handling.
- ▶ Avoid contact with incompatible materials.
- ▶ Keep containers securely sealed.
- ▶ Avoid physical damage to containers.
- ▶ Always wash hands with soap and water after handling.
- ▶ Work clothes should be laundered separately.
- ▶ Use good occupational work practice.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.
- ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

## MIROBILD AC 3722

## Other information

- ▶ Store in original containers in approved flame-proof area.
- ▶ No smoking, naked lights, heat or ignition sources.
- ▶ **DO NOT store in pits, depressions, basements or areas where vapours may be trapped.**
- ▶ Keep containers securely sealed.
- ▶ Store away from incompatible materials in a cool, dry well ventilated area.
- ▶ Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

## Conditions for safe storage, including any incompatibilities

## Suitable container

- ▶ Packing as supplied by manufacturer.
- ▶ Plastic containers may only be used if approved for flammable liquid.
- ▶ Check that containers are clearly labelled and free from leaks.
- ▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- ▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- ▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- ▶ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.
- ▶ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- ▶ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

## Storage incompatibility

- ▶ Avoid reaction with oxidising agents
- ▶ Avoid strong acids, bases.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

## Control parameters

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

## INGREDIENT DATA

| Source   | Ingredient          | Material name  | TWA  | STEL                            | Peak                           | Notes   |
|--|---------------------|--|--|---------------------------------|--------------------------------|---|
| New Zealand Workplace Exposure Standards (WES) | talc                | Talc (containing no asbestos fibres) / Talc (containing asbestos fibres) | 2 Respirable dust mg/m <sup>3</sup>                    | Not Available                   | Not Available                  | Not Available   |
| New Zealand Workplace Exposure Standards (WES) | n-butanol           | n-Butyl alcohol  | Not Available  | Not Available                   | 150 mg/m <sup>3</sup> / 50 ppm | Skin absorption   |
| New Zealand Workplace Exposure Standards (WES) | nitrocellulose      | Particulates not otherwise classified                                    | 10 Inhalable dust; 3 Respirable dust mg/m <sup>3</sup> | Not Available                   | Not Available                  | Not Available   |
| New Zealand Workplace Exposure Standards (WES) | methyl ethyl ketone | Methyl ethyl ketone  | 445 mg/m <sup>3</sup> / 150 ppm                        | 890 mg/m <sup>3</sup> / 300 ppm | Not Available                  | Exposure can also be estimated by biological monitoring.                          |
| New Zealand Workplace Exposure Standards (WES) | ethyl acetate       | Ethyl acetate  | 720 mg/m <sup>3</sup> / 200 ppm                        | Not Available                   | Not Available                  | Not Available   |
| New Zealand Workplace Exposure Standards (WES) | n-butyl acetate     | n-Butyl acetate  | 713 mg/m <sup>3</sup> / 150 ppm                        | 950 mg/m <sup>3</sup> / 200 ppm | Not Available                  | Not Available   |
| New Zealand Workplace Exposure Standards (WES) | titanium dioxide    | Titanium dioxide   | 10 mg/m <sup>3</sup>                                   | Not Available                   | Not Available                  | The value for inhalable dust containing no asbestos and less than 1% free silica. |
| New Zealand Workplace Exposure Standards (WES) | xylene              | Xylene (o-, m-, p-isomers)   | 217 mg/m <sup>3</sup> / 50 ppm                         | Not Available                   | Not Available                  | Not Available   |

## EMERGENCY LIMITS

| Ingredient          | Material name                            | TEEL-1               | TEEL-2                | TEEL-3                |
|---------------------|--|----------------------|-----------------------|-----------------------|
| talc                | Talc                                     | 2 mg/m <sup>3</sup>  | 2 mg/m <sup>3</sup>   | 2.6 mg/m <sup>3</sup> |
| n-butanol           | Butyl alcohol, n-; (n-Butanol)           | 20 ppm               | 50 ppm                | 8000 ppm              |
| nitrocellulose      | Pyroxylin; (Cellulose tetranitrate)      | 15 mg/m <sup>3</sup> | 170 mg/m <sup>3</sup> | 990 mg/m <sup>3</sup> |
| methyl ethyl ketone | Butanone, 2-; (Methyl ethyl ketone; MEK) | Not Available        | Not Available         | Not Available         |
| ethyl acetate       | Ethyl acetate                            | 400 ppm              | 400 ppm               | 10000 ppm             |
| n-butyl acetate     | Butyl acetate, n-                        | Not Available        | Not Available         | Not Available         |
| titanium dioxide    | Titanium oxide; (Titanium dioxide)       | 10 mg/m <sup>3</sup> | 10 mg/m <sup>3</sup>  | 10 mg/m <sup>3</sup>  |
| xylene              | Xylenes                                  | Not Available        | Not Available         | Not Available         |

| Ingredient          | Original IDLH                     | Revised IDLH            |
|---------------------|-----------------------------------|-------------------------|
| talc                | N.E. mg/m <sup>3</sup> / N.E. ppm | 1,000 mg/m <sup>3</sup> |
| resins              | Not Available                     | Not Available           |
| n-butanol           | 8,000 ppm                         | 1,400 [LEL] ppm         |
| nitrocellulose      | Not Available                     | Not Available           |
| methyl ethyl ketone | 3,000 ppm                         | 3,000 [Unch] ppm        |
| ethyl acetate       | 10,000 ppm                        | 2,000 [LEL] ppm         |
| n-butyl acetate     | 10,000 ppm                        | 1,700 [LEL] ppm         |
| titanium dioxide    | N.E. mg/m <sup>3</sup> / N.E. ppm | 5,000 mg/m <sup>3</sup> |

Continued...

## MIROBILD AC 3722

|   |               |               |
|---|---------------|---------------|
| N-tallow(alkyl)-1,3-propanediamine dioleate | Not Available | Not Available |
| xylene                                      | 1,000 ppm     | 900 ppm       |

**MATERIAL DATA**

For talc (a form of magnesium silicate):

Most health problems associated with occupational exposure to talcs appear to evolve mostly from the nonplatform content of the talc being mined or milled (being the asbestos-like amphiboles, serpentines (asbestiformes) and other minerals in the form of acicular, prismatic and fibrous crystals including, possibly, asbestos).

Because of severe health effects associated with exposures to asbestos, regulatory agencies tend to regard all elongate mineral crystal particles, whether prismatic, acicular, fibrous, as asbestos - the only provision is the particles have an aspect ratio (length to diameter) of 3:1 or greater.

Consideration is also given to their respirability, their width being less than or equal to 3 µm. Only limited data, however, exists on the health effects of elongate mineral particles having prismatic, acicular or fibrous (non-asbestos) forms. Experimental evidence indicates that the carcinogen potential of mineral fibres is related to the size class with diameter of 8 µm with shorter, thicker particles having little biological activity.

Dust of nonfibrous talc, consisting entirely of platform talc crystals and containing no asbestos poses a relatively small respiratory hazard.

Difficulties exist, however, in the determination of asbestos as cleavage fragments of prismatic or acicular crystals, nonasbestos fibres and asbestos fibres are very similar.

Subject to an accurate determination of asbestos and crystalline silica, exposure at or below the recommended TLV-TWA, is thought to protect workers from the significant risk of nonmalignant respiratory effects associated with talc dusts.

For ethyl acetate:

Odour Threshold Value: 6.4-50 ppm (detection), 13.3-75 ppm (recognition)

The TLV-TWA provides a significant margin of safety from the standpoint of adverse health effects. Unacclimated subjects found the odour objectionably strong at 200 ppm. Mild nose, eye and throat irritation was experienced at 400 ppm. Workers exposed regularly at concentrations ranging from 375 ppm to 1500 ppm for several months showed no unusual signs or symptoms.

Odour Safety Factor(OSF)

OSF=51 (ETHYL ACETATE)

For n-butyl acetate

Odour Threshold Value: 0.0063 ppm (detection), 0.038-12 ppm (recognition)

Exposure at or below the recommended TLV-TWA is thought to prevent significant irritation of the eyes and respiratory passages as well as narcotic effects. In light of the lack of substantive evidence regarding teratogenicity and a review of acute oral data a STEL is considered inappropriate.

Odour Safety Factor(OSF)

OSF=3.8E2 (n-BUTYL ACETATE)

Animals exposed by inhalation to 10 mg/m3 titanium dioxide show no significant fibrosis, possibly reversible tissue reaction. The architecture of lung air spaces remains intact.

For toluene:

Odour Threshold Value: 0.16-6.7 (detection), 1.9-69 (recognition)

NOTE: Detector tubes measuring in excess of 5 ppm, are available.

High concentrations of toluene in the air produce depression of the central nervous system (CNS) in humans. Intentional toluene exposure (glue-sniffing) at maternally-intoxicating concentration has also produced birth defects. Foetotoxicity appears at levels associated with CNS narcosis and probably occurs only in those with chronic toluene-induced kidney failure. Exposure at or below the recommended TLV-TWA is thought to prevent transient headache and irritation, to provide a measure of safety for possible disturbances to human reproduction, the prevention of reductions in cognitive responses reported amongst humans inhaling greater than 40 ppm, and the significant risks of hepatotoxic, behavioural and nervous system effects (including impaired reaction time and incoordination). Although toluene/ethanol interactions are well recognised, the degree of protection afforded by the TLV-TWA among drinkers is not known.

Odour Safety Factor(OSF)

OSF=17 (TOLUENE)

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

Xylene vapour is an irritant to the eyes, mucous membranes and skin and causes narcosis at high concentrations. Exposure to doses sufficiently high to produce intoxication and unconsciousness also produces transient liver and kidney toxicity. Neurologic impairment is NOT evident amongst volunteers inhaling up to 400 ppm though complaints of ocular and upper respiratory tract irritation occur at 200 ppm for 3 to 5 minutes.

Exposure to xylene at or below the recommended TLV-TWA and STEL is thought to minimise the risk of irritant effects and to produce neither significant narcosis or chronic injury. An earlier skin notation was deleted because percutaneous absorption is gradual and protracted and does not substantially contribute to the dose received by inhalation.

Odour Safety Factor(OSF)

OSF=4 (XYLENE)

For n-butanol:

Odour Threshold Value: 0.12-3.4 ppm (detection), 1.0-3.5 ppm (recognition)

NOTE: Detector tubes for n-butanol, measuring in excess of 5 ppm are commercially available.

Exposure at or below the TLV-TWA is thought to provide protection against hearing loss due to vestibular and auditory nerve damage in younger workers and to protect against the significant risk of headache and irritation.

25 ppm may produce mild irritation of the respiratory tract 50 ppm may produce headache and vertigo.

Higher concentrations may produce marked irritation, sore throat, coughing, nausea, shortness of breath, pulmonary injury and central nervous system depression characterised by headache, dizziness, dullness and drowsiness.

6000 ppm may produce giddiness, prostration, narcosis, ataxia, and death.

Odour Safety Factor (OSF)

OSF=60 (n-BUTANOL)

For isobutanol:

Odour Threshold Value: 0.66-40 ppm (detection), 1.8-53 ppm (recognition) Although there do not appear to be reports of isobutyl alcohol causing auditory impairment or vestibular damage in humans (as with n-butanol) the recommended TLV-TWA recognises the slightly greater acute toxic potential of isobutanol versus n-butanol. Exposure at or below this limit is thought to significantly reduce the risk of skin irritation.

Odour Safety Factor (OSF)

OSF=31 (ISOBUTYL ALCOHOL)

For methyl ethyl ketone:

Odour Threshold Value: Various reported as 2 ppm and 4.8 ppm

Odour threshold: 2 ppm (detection); 5 ppm (recognition) 25 ppm (easy recognition); 300 ppm IRRITATING

Exposures at or below the recommended TLV-TWA are thought to prevent injurious systemic effects and to minimise objections to odour and irritation. Where synergism or potentiation may occur stringent control of the primary toxin (e.g. n-hexane or methyl butyl ketone) is desirable and additional consideration should be given to lowering MEK exposures.


Odour Safety Factor(OSF)

OSF=28 (METHYL ETHYL KETONE)

**Exposure controls**



## MIROBILD AC 3722

| <p><b>Appropriate engineering controls</b></p>  | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1"> <thead> <tr> <th>Type of Contaminant:</th><th>Air Speed:</th></tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td><td>0.25-0.5 m/s<br/>(50-100 f/min.)</td></tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td><td>0.5-1 m/s<br/>(100-200 f/min.)</td></tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td><td>1-2.5 m/s<br/>(200-500 f/min.)</td></tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th><th>Upper end of the range</th></tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td><td>1: Disturbing room air currents</td></tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td><td>2: Contaminants of high toxicity</td></tr> <tr> <td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr> <tr> <td>4: Large hood or large air mass in motion</td><td>4: Small hood-local control only</td></tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s<br>(50-100 f/min.) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s<br>(200-500 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
|---|---|----------------------|------------|--|---------------------------------|---|-------------------------------|--|-------------------------------|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
| Type of Contaminant:  | Air Speed:  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s<br>(50-100 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s<br>(200-500 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Lower end of the range  | Upper end of the range  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Personal protection</b></p>   |    |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Eye and face protection</b></p>   | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Skin protection</b></p>   | <p>See Hand protection below</p>  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Hands/feet protection</b></p>   | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>▶ frequency and duration of contact,</li> <li>▶ chemical resistance of glove material,</li> <li>▶ glove thickness and</li> <li>▶ dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>▶ When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>▶ When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>▶ Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>▶ Contaminated gloves should be replaced.</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p>   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Body protection</b></p>   | <p>See Other protection below</p>   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |



## MIROBILD AC 3722

|                  |   |
|------------------|---|
| Other protection | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> </ul> <p>Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</p> |
|                  |   |
| Thermal hazards  | Not Available   |

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

MIROBILD AC 3722

| Material          | CPI     |
|-------------------|---------|
| ##ethyl           | acetate |
| ##n-butyl         | acetate |
| BUTYL             | C       |
| BUTYL/NEOPRENE    | C       |
| CPE               | C       |
| HYPALON           | C       |
| NAT+NEOPR+NITRILE | C       |
| NATURAL RUBBER    | C       |
| NATURAL+NEOPRENE  | C       |
| NEOPRENE          | C       |
| NEOPRENE/NATURAL  | C       |
| NITRILE           | C       |
| NITRILE+PVC       | C       |
| PE                | C       |
| PE/EVAL/PE        | C       |
| PVA               | C       |
| PVC               | C       |
| PVDC/PE/PVDC      | C       |
| SARANEX-23        | C       |
| SARANEX-23 2-PLY  | C       |
| TEFLON            | C       |
| VITON             | C       |
| VITON/BUTYL       | C       |
| VITON/CHLOROBUTYL | C       |
| VITON/NEOPRENE    | C       |
| ##methyl ethyl    | ketone  |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## Respiratory protection

Type KAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator    |
|------------------------------------|----------------------|----------------------|---------------------------|
| up to 5 x ES                       | KAX-AUS / Class 1 P2 | -                    | KAX-PAPR-AUS / Class 1 P2 |
| up to 25 x ES                      | Air-line*            | KAX-2 P2             | KAX-PAPR-2 P2             |
| up to 50 x ES                      | -                    | KAX-3 P2             | -                         |
| 50+ x ES                           | -                    | Air-line**           | -                         |

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

|                |  |   |               |
|----------------|--|---|---------------|
| Appearance     | White flammable liquid with a strong solvent odour; partially miscible with water. |   |               |
| Physical state | Liquid   | Relative density (Water = 1)            | 1.23-1.28     |
| Odour          | Not Available  | Partition coefficient n-octanol / water | Not Available |

Continued...

## MIROBILD AC 3722

|  |                   |                                  |                           |
|--|-------------------|----------------------------------|---------------------------|
| Odour threshold                              | Not Available     | Auto-ignition temperature (°C)   | Not Available             |
| pH (as supplied)                             | Not Applicable    | Decomposition temperature        | Not Available             |
| Melting point / freezing point (°C)          | Not Available     | Viscosity (cSt)                  | Not Available             |
| Initial boiling point and boiling range (°C) | Not Available     | Molecular weight (g/mol)         | Not Applicable            |
| Flash point (°C)                             | -6.7              | Taste                            | Not Available             |
| Evaporation rate                             | Not Available     | Explosive properties             | Not Available             |
| Flammability                                 | HIGHLY FLAMMABLE. | Oxidising properties             | Not Available             |
| Upper Explosive Limit (%)                    | Not Available     | Surface Tension (dyn/cm or mN/m) | Not Available             |
| Lower Explosive Limit (%)                    | Not Available     | Volatile Component (%vol)        | 40-45 (VOC = 500-550 g/l) |
| Vapour pressure (kPa)                        | Not Available     | Gas group                        | Not Available             |
| Solubility in water (g/L)                    | Immiscible        | pH as a solution (1%)            | Not Applicable            |
| Vapour density (Air = 1)                     | >1                | VOC g/L                          | Not Available             |

## SECTION 10 STABILITY AND REACTIVITY

|                                    |  |
|------------------------------------|--|
| Reactivity                         | See section 7  |
| Chemical stability                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| Possibility of hazardous reactions | See section 7  |
| Conditions to avoid                | See section 7  |
| Incompatible materials             | See section 7  |
| Hazardous decomposition products   | See section 5  |

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

|           |   |
|-----------|---|
| Inhaled   | <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.</p> <p>The acute toxicity of inhaled alkylbenzenes is best described by central nervous system depression. As a rule, these compounds may also act as general anaesthetics.</p> <p>Systemic poisoning produced by general anaesthesia is characterised by lightheadedness, nervousness, apprehension, euphoria, confusion, dizziness, drowsiness, tinnitus, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness and respiratory depression and arrest. Cardiac arrest may result from cardiovascular collapse. Bradycardia, and hypotension may also be produced.</p> <p>Inhaled alkylbenzene vapours cause death in animals at air levels that are relatively similar (typically LC50s are in the range 5000 -8000 ppm for 4 to 8 hour exposures). It is likely that acute inhalation exposure to alkylbenzenes resembles that to general anaesthetics.</p> <p>Alkylbenzenes are not generally toxic other than at high levels of exposure. This may be because their metabolites have a low order of toxicity and are easily excreted. There is little or no evidence to suggest that metabolic pathways can become saturated leading to spillover to alternate pathways. Nor is there evidence that toxic reactive intermediates, which may produce subsequent toxic or mutagenic effects, are formed</p> <p>Human subjects exposed to 24 ppm n-butanol experienced mild irritation which became objectionable. Headaches were reported at 50 ppm.</p> <p>Exposure by mice to 6600 ppm produced signs of marked central nervous system (CNS) depression, including prostration after 2 hours, narcosis after 3 hours and some deaths.</p> <p>Although n-butanol is odourous and generally possesses adequate warning properties, the olfactory senses may become fatigued.</p> <p>Exposure to aliphatic alcohols with more than 3 carbons may produce central nervous system effects such as headache, dizziness, drowsiness, muscle weakness, delirium, CNS depression, coma, seizure, and neurobehavioural changes. Symptoms are more acute with higher alcohols. Respiratory tract involvement may produce irritation of the mucosa, respiratory insufficiency, respiratory depression secondary to CNS depression, pulmonary oedema, chemical pneumonitis and bronchitis. Cardiovascular involvement may result in arrhythmias and hypotension. Gastrointestinal effects may include nausea and vomiting. Kidney and liver damage may result following massive exposures. The alcohols are potential irritants being, generally, stronger irritants than similar organic structures that lack functional groups (e.g. alkanes) but are much less irritating than the corresponding amines, aldehydes or ketones. Alcohols and glycols (diols) rarely represent serious hazards in the workplace, because their vapour concentrations are usually less than the levels which produce significant irritation which, in turn, produce significant central nervous system effects as well.</p> <p>Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination</p> |
| Ingestion | <p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging, pulmonary oedema, progressing to chemical pneumonitis; serious consequences may result.</p> <p>Signs and symptoms of chemical (aspiration) pneumonitis may include coughing, gasping, choking, burning of the mouth, difficult breathing, and bluish coloured skin (cyanosis).</p> <p>Effects on the nervous system characterise over-exposure to higher aliphatic alcohols. These include headache, muscle weakness, giddiness, ataxia, (loss of muscle coordination), confusion, delirium and coma. Gastrointestinal effects may include nausea, vomiting and diarrhoea. In the absence of effective treatment, respiratory arrest is the most common cause of death in animals acutely poisoned by the higher alcohols. Aspiration of liquid alcohols produces an especially toxic response as they are able to penetrate deeply in the lung where they are absorbed and may produce pulmonary injury. Those possessing lower viscosity elicit a greater response. The result is a high blood level and prompt death at doses otherwise tolerated by ingestion without aspiration. In general the</p>  |

## MIROBILD AC 3722

|                            |  |                                    |
|----------------------------|--|------------------------------------|
|                            | <p>secondary alcohols are less toxic than the corresponding primary isomers. As a general observation, alcohols are more powerful central nervous system depressants than their aliphatic analogues. In sequence of decreasing depressant potential, tertiary alcohols with multiple substituent OH groups are more potent than secondary alcohols, which, in turn, are more potent than primary alcohols. The potential for overall systemic toxicity increases with molecular weight (up to C7), principally because the water solubility is diminished and lipophilicity is increased.</p> <p>Within the homologous series of aliphatic alcohols, narcotic potency may increase even faster than lethality</p> <p>Only scanty toxicity information is available about higher homologues of the aliphatic alcohol series (greater than C7) but animal data establish that lethality does not continue to increase with increasing chain length. Aliphatic alcohols with 8 carbons are less toxic than those immediately preceding them in the series. 10 -Carbon n-decyl alcohol has low toxicity as do the solid fatty alcohols (e.g. lauryl, myristyl, cetyl and stearyl). However the rat aspiration test suggests that decyl and melted dodecyl (lauryl) alcohols are dangerous if they enter the trachea. In the rat even a small quantity (0.2 ml) of these behaves like a hydrocarbon solvent in causing death from pulmonary oedema.</p> <p>Primary alcohols are metabolised to corresponding aldehydes and acids; a significant metabolic acidosis may occur. Secondary alcohols are converted to ketones, which are also central nervous system depressants and which, in he case of the higher homologues persist in the blood for many hours. Tertiary alcohols are metabolised slowly and incompletely so their toxic effects are generally persistent.</p>   |                                    |
| <b>Skin Contact</b>        | <p>Skin contact with the material may be harmful; systemic effects may result following absorption.</p> <p>The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either</p> <ul style="list-style-type: none"> <li>► produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or</li> <li>► produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.</li> </ul> <p>Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p>   |                                    |
| <b>Eye</b>                 | <p>When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.</p> <p>Workers exposed to 200 ppm n-butanol showed ocular symptoms including corneal inflammation, burning sensation, blurring of vision, lachrymation, and photophobia. 100 ppm produced no systemic effects and reports of irritation of the eyes was rare.</p>  |                                    |
| <b>Chronic</b>             | <p>On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.</p> <p>Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.</p> <p>Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.</p> <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p> <p>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.</p> <p>Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population.</p> <p>Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.</p> <p>There is some evidence that human exposure to the material may result in developmental toxicity. This evidence is based on animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects.</p> <p>Serious systemic effects from exposure to n-butanol in the form of auditory and vestibular nerve damage have been reported amongst workers in France and Mexico. Audiologic impairment was produced in workers exposed to 80 ppm n-butanol with unprotected noise exposure. Workers exposed over a 15 year period (1929-1944) exhibited severe vertigo and vertiges gravis. Workers exposed from 3-11 years without personal protective equipment from noise experienced greater hearing loss (hypoaacusia) in direct relation to exposure time when compared to a control group exposed to industrial noise of 90-100 dB but with n-butanol exposure. Average hearing loss was not large but the workers had central frequencies of 21.98 dB (11.59 dB minimum and 32.30 dB maximum) with a mean widening of the break between 3000 and 4000 Hz of 42.22 dB. There was a tendency of the averages to decrease as the frequencies moved away from the central zone. Affected workers were aged from 20-39 years. [ACGIH Documentation of TLVs]</p> <p>Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).</p> |                                    |
| <b>MIROBILD AC 3722</b>    | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|                            | Not Available  | Not Available                      |
| <b>talc</b>                | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|                            | Not Available  | Skin (human): 0.3 mg/3d-I mild     |
| <b>n-butanol</b>           | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|                            | Dermal (rabbit) LD50: 3434.4 mg/kg <sup>[1]</sup>  | Eye (human): 50 ppm - irritant     |
|                            | Inhalation (rat) LC50: 24 mg/L/4h <sup>[2]</sup>   | Eye (rabbit): 1.6 mg-SEVERE        |
|                            | Inhalation (rat) LC50: 8000 ppm/4hE <sup>[2]</sup>   | Eye (rabbit): 24 mg/24h-SEVERE     |
|                            | Oral (rat) LD50: 2292.3 mg/kg <sup>[1]</sup>   | Skin (rabbit): 405 mg/24h-moderate |
| <b>nitrocellulose</b>      | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|                            | Oral (rat) LD50: >5000 mg/kg <sup>[2]</sup>  | Not Available                      |
| <b>methyl ethyl ketone</b> | <b>TOXICITY</b>  | <b>IRRITATION</b>                  |
|                            | Dermal (rabbit) LD50: >8100 mg/kg <sup>[1]</sup>   | - mild                             |
|                            | Inhalation (rat) LC50: 23.5 mg/L/8h <sup>[2]</sup>   | Eye (human): 350 ppm -irritant     |
|                            | Inhalation (rat) LC50: 50.1 mg/L/8 hr <sup>[2]</sup>   | Eye (rabbit): 80 mg - irritant     |
|                            | Oral (rat) LD50: 3474.9 mg/kg <sup>[1]</sup>   | Skin (rabbit): 402 mg/24 hr - mild |
|                            |  | Skin (rabbit):13.78mg/24 hr open   |

## MIROBILD AC 3722

| ethyl acetate                               | TOXICITY   | IRRITATION   |
|---|--|--|
|   | Dermal (rabbit) LD50: >18000 mg/kg <sup>[2]</sup>    | Eye (human): 400 ppm   |
|   | Inhalation (mouse) LC50: >18 mg/l4 h <sup>[1]</sup>  |  |
|   | Inhalation (mouse) LC50: 33.5 mg/l2 h <sup>[1]</sup> |  |
|   | Inhalation (mouse) LC50: 45 mg/L/2H <sup>[2]</sup>   |  |
|   | Inhalation (rat) LC50: >6000 ppm/6H <sup>[2]</sup>   |  |
|   | Inhalation (rat) LC50: 1600 ppm/8h <sup>[2]</sup>    |  |
|   | Inhalation (rat) LC50: 200 mg/l1 h <sup>[1]</sup>    |  |
| n-butyl acetate                             | TOXICITY   | IRRITATION   |
|   | Dermal (rabbit) LD50: >14080 mg/kg <sup>[1]</sup>    | * [PPG]  |
|   | Inhalation (rat) LC50: 2000 ppm/4Hg <sup>[2]</sup>   | Eye (human): 300 mg  |
|   | Inhalation (rat) LC50: 390 ppm/4h <sup>[2]</sup>     | Eye (rabbit): 20 mg (open)-SEVERE  |
|   | Oral (rat) LD50: 10736 mg/kg <sup>[1]</sup>          | Eye (rabbit): 20 mg/24h - moderate<br>Skin (rabbit): 500 mg/24h-moderate |
| titanium dioxide                            | TOXICITY   | IRRITATION   |
|   | Inhalation (rat) LC50: >2.28 mg/l4 h <sup>[1]</sup>  | Skin (human): 0.3 mg /3D (int)-mild *                                    |
|   | Inhalation (rat) LC50: >3.56 mg/l4 h <sup>[1]</sup>  |  |
|   | Inhalation (rat) LC50: >6.82 mg/l4 h <sup>[1]</sup>  |  |
|   | Inhalation (rat) LC50: 3.43 mg/l4 h <sup>[1]</sup>   |  |
|   | Inhalation (rat) LC50: 5.09 mg/l4 h <sup>[1]</sup>   |  |
| N-tallow(alkyl)-1,3-propanediamine dioleate | TOXICITY   | IRRITATION   |
|   | Oral (rat) LD50: >5000 mg/kg <sup>[2]</sup>          | Eye: corrosive [Akzo]<br>Skin: corrosive                                 |
| xylene                                      | TOXICITY   | IRRITATION   |
|   | Dermal (rabbit) LD50: >1700 mg/kg <sup>[2]</sup>     | Eye (human): 200 ppm irritant  |
|   | Inhalation (rat) LC50: 5000 ppm/4h <sup>[2]</sup>    | Eye (rabbit): 5 mg/24h SEVERE  |
|   | Oral (rat) LD50: 4300 mg/kg <sup>[2]</sup>           | Eye (rabbit): 87 mg mild<br>Skin (rabbit): 500 mg/24h moderate           |

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

**MIROBILD AC 3722**

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

No significant acute toxicological data identified in literature search.

For talc (a form of magnesium silicate)

The overuse of talc in nursing infants has resulted in pulmonary oedema, pneumonia and death within hours of inhaling talcum powder. The powder dries the mucous membranes of the bronchioles, disrupts pulmonary clearance, clogs smaller airways. Victims display wheezing, rapid or difficult breathing, increased pulse, cyanosis, fever. Mild exposure may cause relatively minor inflammatory lung disease.

Long term exposure may show wheezing, weakness, productive cough, limited chest expansion, scattered rales, cyanosis.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and

## MIROBILD AC 3722

|                     |  |
|---------------------|--|
|                     | intracellular oedema of the epidermis.   |
| TALC                | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. No significant acute toxicological data identified in literature search.</p> <p>For talc (a form of magnesium silicate)</p> <p>The overuse of talc in nursing infants has resulted in pulmonary oedema, pneumonia and death within hours of inhaling talcum powder. The powder dries the mucous membranes of the bronchioles, disrupts pulmonary clearance, clogs smaller airways. Victims display wheezing, rapid or difficult breathing, increased pulse, cyanosis, fever. Mild exposure may cause relatively minor inflammatory lung disease.</p> <p>Long term exposure may show wheezing, weakness, productive cough, limited chest expansion, scattered rales, cyanosis.</p> <p>The substance is classified by IARC as Group 3:<br/> <b>NOT</b> classifiable as to its carcinogenicity to humans.<br/> Evidence of carcinogenicity may be inadequate or limited in animal testing.</p>  |
| N-BUTANOL           | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p> <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p>for n-butanol</p> <p><b>Acute toxicity:</b> n-Butanol (BA) was only slightly toxic to experimental animals following acute oral, dermal, or inhalation exposure. The acute oral LD50 values for female rats ranged from 790 to 4360 mg/kg. Different strains of rat were used in each of four studies, which may account for the variability. Oral LD50 values for mice, rabbits, hamsters, dogs, and male rats all fell within the same range. The rat inhalation LC0 of 8000 ppm (24000 mg/m3) indicates very low inhalation toxicity (no lethality at 8000 ppm). The rabbit dermal LD50 was 3402 mg/kg, indicating that BA can penetrate the skin, but not very readily. Animal experiments and human experience indicate that BA is, at most, moderately irritating to the skin, but it is a severe eye irritant. These effects are most likely due to BA's localised defatting and drying characteristics. Although no animal data are available, human studies and experience show that BA is not likely to be a skin sensitiser.</p> <p>The median odor threshold for BA (0.17 ppm) is well below the lowest nasal irritation threshold in humans (289 ppm), allowing warning of possible chemical exposure prior to nasal irritation occurring. Human studies are complicated by the odor characteristics of the material, as the odor threshold is well below the levels at which irritation is observed.</p> <p><b>Repeat dose toxicity:</b> An in vivo toxicokinetics study confirmed the rapid metabolism of n-butyl acetate (BAc) to BA. Hydrolysis of BAc in blood and brain was estimated to be 99 percent complete within 2.7 minutes (elimination t1/2 = 0.41 minute). Thus, organisms exposed to BAc can experience appreciable tissue concentrations of BA. In this way, the results of toxicity studies with BAc can be used as supplemental, surrogate data to provide information on the toxicity of BA.</p> <p>A thirteen-week, subchronic exposure to BAc, the metabolic precursor of BA, produced transient hypoactivity (during exposure only) at 1500 and 3000 ppm (7185 and 14370 mg/m3) along with decreased body weight and food consumption, but no post exposure neurotoxicity even at 3000 ppm. A concurrent subchronic neurotoxicity study under the same exposure conditions showed no evidence of cumulative neurotoxicity based upon functional observational battery endpoints, quantitative motor activity, neuropathology and scheduled-controlled operant behavior endpoints. A no observable effect level (NOAEL) of 500 ppm (2395 mg/m3) was reported for systemic effects in rats, and a NOAEL of 3000 ppm (14370 mg/m3) was reported for post exposure neurotoxicity in rats.</p> <p><b>Reproductive toxicity:</b> Several studies indicate that BA is not a reproductive toxicant.</p> <p>Female rats exposed to 6000 ppm (18000 mg/m3) BA throughout gestation and male rats exposed to 6000 ppm (18000 mg/m3) BA for six weeks prior to mating showed no effects on fertility or pregnancy rate. Male rats given BA at 533 mg/kg/day for 5 days had no testicular toxicity.</p> <p><b>Developmental toxicity:</b> BA produced only mild foetotoxicity and developmental alterations at or near the maternally toxic (even lethal) dose of 8000 ppm (24000 mg/m3) throughout gestation.</p> <p><b>Genotoxicity:</b> An entire battery of negative in vitro tests and a negative in vivo micronucleus test indicate that BA is not genotoxic.</p> <p><b>Carcinogenicity:</b> Based upon the battery of negative mutagenicity and clastogenicity findings, BA presents a very small potential for carcinogenicity.</p> |
| NITROCELLULOSE      | No significant acute toxicological data identified in literature search.   |
| METHYL ETHYL KETONE | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p>Methyl ethyl ketone is considered to have a low order of toxicity; however methyl ethyl ketone is often used in combination with other solvents and the toxic effects of the mix may be greater than either solvent alone. Combinations of n-hexane with methyl ethyl ketone and also methyl n-butyl ketone with methyl ethyl ketone show increase in peripheral neuropathy, a progressive disorder of nerves of extremities.</p> <p>Combinations with chloroform also show increase in toxicity</p>  |
| N-BUTYL ACETATE     | <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p>  |



## MIROBILD AC 3722

## TITANIUM DIOXIDE

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

For titanium dioxide:

Humans can be exposed to titanium dioxide via inhalation, ingestion or dermal contact. In human lungs, the clearance kinetics of titanium dioxide is poorly characterized relative to that in experimental animals. (General particle characteristics and host factors that are considered to affect deposition and retention patterns of inhaled, poorly soluble particles such as titanium dioxide are summarized in the monograph on carbon black.) With regard to inhaled titanium dioxide, human data are mainly available from case reports that showed deposits of titanium dioxide in lung tissue as well as in lymph nodes. A single clinical study of oral ingestion of fine titanium dioxide showed particle size-dependent absorption by the gastrointestinal tract and large interindividual variations in blood levels of titanium dioxide. Studies on the application of sunscreens containing ultrafine titanium dioxide to healthy skin of human volunteers revealed that titanium dioxide particles only penetrate into the outermost layers of the stratum corneum, suggesting that healthy skin is an effective barrier to titanium dioxide. There are no studies on penetration of titanium dioxide in compromised skin.

Respiratory effects that have been observed among groups of titanium dioxide-exposed workers include decline in lung function, pleural disease with plaques and pleural thickening, and mild fibrotic changes. However, the workers in these studies were also exposed to asbestos and/or silica.

No data were available on genotoxic effects in titanium dioxide-exposed humans.

Many data on deposition, retention and clearance of titanium dioxide in experimental animals are available for the inhalation route. Titanium dioxide inhalation studies showed differences — both for normalized pulmonary burden (deposited mass per dry lung, mass per body weight) and clearance kinetics — among rodent species including rats of different size, age and strain. Clearance of titanium dioxide is also affected by pre-exposure to gaseous pollutants or co-exposure to cytotoxic aerosols. Differences in dose rate or clearance kinetics and the appearance of focal areas of high particle burden have been implicated in the higher toxic and inflammatory lung responses to intratracheally instilled vs inhaled titanium dioxide particles. Experimental studies with titanium dioxide have demonstrated that rodents experience dose-dependent impairment of alveolar macrophage-mediated clearance. Hamsters have the most efficient clearance of inhaled titanium dioxide. Ultrafine primary particles of titanium dioxide are more slowly cleared than their fine counterparts.

Titanium dioxide causes varying degrees of inflammation and associated pulmonary effects including lung epithelial cell injury, cholesterol granulomas and fibrosis. Rodents experience stronger pulmonary effects after exposure to ultrafine titanium dioxide particles compared with fine particles on a mass basis.

These differences are related to lung burden in terms of particle surface area, and are considered to result from impaired phagocytosis and sequestration of ultrafine particles into the interstitium.

Fine titanium dioxide particles show minimal cytotoxicity to and inflammatory/pro-fibrotic mediator release from primary human alveolar macrophages in vitro compared with other particles. Ultrafine titanium dioxide particles inhibit phagocytosis of alveolar macrophages in vitro at mass dose concentrations at which this effect does not occur with fine titanium dioxide. In-vitro studies with fine and ultrafine titanium dioxide and purified DNA show induction of DNA damage that is suggestive of the generation of reactive oxygen species by both particle types. This effect is stronger for ultrafine than for fine titanium oxide, and is markedly enhanced by exposure to simulated sunlight/ultraviolet light.

#### Animal carcinogenicity data

Pigmentary and ultrafine titanium dioxide were tested for carcinogenicity by oral administration in mice and rats, by inhalation in rats and female mice, by intratracheal administration in hamsters and female rats and mice, by subcutaneous injection in rats and by intraperitoneal administration in male mice and female rats.

In one inhalation study, the incidence of benign and malignant lung tumours was increased in female rats. In another inhalation study, the incidences of lung adenomas were increased in the high-dose groups of male and female rats. Cystic keratinizing lesions that were diagnosed as squamous-cell carcinomas but re-evaluated as non-neoplastic pulmonary keratinizing cysts were also observed in the high-dose groups of female rats. Two inhalation studies in rats and one in female mice were negative.

Intratracheally instilled female rats showed an increased incidence of both benign and malignant lung tumours following treatment with two types of titanium dioxide. Tumour incidence was not increased in intratracheally instilled hamsters and female mice.

In-vivo studies have shown enhanced micronucleus formation in bone marrow and peripheral blood lymphocytes of intraperitoneally instilled mice. Increased Hprt mutations were seen in lung epithelial cells isolated from titanium dioxide-instilled rats. In another study, no enhanced oxidative DNA damage was observed in lung tissues of rats that were intratracheally instilled with titanium dioxide. The results of most in-vitro genotoxicity studies with titanium dioxide were negative.

**WARNING:** This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

\* IUCLID

#### N-TALLOW(ALKYL)-1,3-PROPANEDIAMINE DIOLEATE

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

The material may produce respiratory tract irritation. Symptoms of pulmonary irritation may include coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and a burning sensation.

Unlike most organs, the lung can respond to a chemical insult or a chemical agent, by first removing or neutralising the irritant and then repairing the damage (inflammation of the lungs may be a consequence).

The repair process (which initially developed to protect mammalian lungs from foreign matter and antigens) may, however, cause further damage to the lungs (fibrosis for example) when activated by hazardous chemicals. Often, this results in an impairment of gas exchange, the primary function of the lungs. Therefore prolonged exposure to respiratory irritants may cause sustained breathing difficulties.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

Tallow derivatives used in the manufacture of cosmetic products such as fatty acids, glycerol, fatty acid esters and soap are regarded as safe if they are obtained by the following minimal processes which must be strictly certified:

- transesterification or hydrolysis at 200C, under pressure for 20 minutes (glycerol and fatty acids and esters)
- saponification with NaOH 12M (glycerol and soap)

\* batch process: at 95C for 3 hours

\* continuous process: at 140C, 2 bars for 8 minutes or equivalent.

Moreover, other tallow derivatives (e.g. fatty alcohols, fatty amines, fatty amides) produced from the above mentioned and submitted to further processes are regarded as safe.

Opinion of The Scientific Committee on Cosmetic Products and Non-Food Products intended for Consumers concerning Tallow Derivatives revised and adapted opinion of 24.6.97 adopted by the plenary session of the SCCNFP of 23 September 1998

\*Akzo Nobel Surfactants

#### XYLENE

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and

## MIROBILD AC 3722

intracellular oedema of the epidermis.  
The substance is classified by IARC as Group 3:  
**NOT** classifiable as to its carcinogenicity to humans.  
Evidence of carcinogenicity may be inadequate or limited in animal testing.  
Reproductive effector in rats

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✓ | Carcinogenicity          | ⊗ |
| Skin Irritation/Corrosion         | ✓ | Reproductivity           | ⊗ |
| Serious Eye Damage/Irritation     | ✓ | STOT - Single Exposure   | ✓ |
| Respiratory or Skin sensitisation | ✓ | STOT - Repeated Exposure | ⊗ |
| Mutagenicity                      | ⊗ | Aspiration Hazard        | ⊗ |

Legend: ✗ – Data available but does not fill the criteria for classification  
 ✓ – Data required to make classification available  
 ⊗ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| Ingredient          | Endpoint | Test Duration (hr) | Species                       | Value         | Source |
|---------------------|----------|--------------------|-------------------------------|---------------|--------|
| n-butanol           | EC50     | 48                 | Crustacea                     | >500mg/L      | 1      |
| n-butanol           | LC50     | 96                 | Fish                          | 88.462mg/L    | 3      |
| n-butanol           | BCF      | 24                 | Fish                          | 921mg/L       | 4      |
| n-butanol           | EC50     | 504                | Crustacea                     | 18mg/L        | 2      |
| n-butanol           | NOEC     | 504                | Crustacea                     | 4.1mg/L       | 2      |
| n-butanol           | EC50     | 96                 | Algae or other aquatic plants | 225mg/L       | 2      |
| nitrocellulose      | EC50     | 96                 | Algae or other aquatic plants | 579mg/L       | 4      |
| methyl ethyl ketone | EC50     | 384                | Crustacea                     | 52.575mg/L    | 3      |
| methyl ethyl ketone | LC50     | 96                 | Fish                          | 228.130mg/L   | 3      |
| methyl ethyl ketone | EC50     | 96                 | Algae or other aquatic plants | >500mg/L      | 4      |
| methyl ethyl ketone | EC50     | 48                 | Crustacea                     | 308mg/L       | 2      |
| methyl ethyl ketone | NOEC     | 48                 | Crustacea                     | 68mg/L        | 2      |
| ethyl acetate       | EC50     | 48                 | Crustacea                     | =164mg/L      | 1      |
| ethyl acetate       | EC50     | 96                 | Algae or other aquatic plants | 4.146mg/L     | 3      |
| ethyl acetate       | LC50     | 96                 | Fish                          | 54.314mg/L    | 3      |
| ethyl acetate       | BCF      | 24                 | Algae or other aquatic plants | 0.05mg/L      | 4      |
| ethyl acetate       | EC0      | 168                | Algae or other aquatic plants | =15mg/L       | 1      |
| ethyl acetate       | NOEC     | 504                | Crustacea                     | 2.4mg/L       | 2      |
| n-butyl acetate     | EC50     | 48                 | Crustacea                     | =32mg/L       | 1      |
| n-butyl acetate     | EC50     | 96                 | Algae or other aquatic plants | 1.675mg/L     | 3      |
| n-butyl acetate     | EC50     | 96                 | Fish                          | 18mg/L        | 2      |
| n-butyl acetate     | LC50     | 96                 | Fish                          | 18mg/L        | 2      |
| n-butyl acetate     | NOEC     | 504                | Crustacea                     | 23mg/L        | 2      |
| titanium dioxide    | LC50     | 96                 | Fish                          | 9.214mg/L     | 3      |
| titanium dioxide    | EC50     | 72                 | Algae or other aquatic plants | 5.83mg/L      | 4      |
| titanium dioxide    | NOEC     | 336                | Fish                          | 0.089mg/L     | 4      |
| titanium dioxide    | EC50     | 48                 | Crustacea                     | 1.23mg/L      | 2      |
| titanium dioxide    | EC50     | 504                | Crustacea                     | 0.46mg/L      | 2      |
| xylene              | EC50     | 24                 | Crustacea                     | 0.711mg/L     | 4      |
| xylene              | LC50     | 96                 | Fish                          | 0.0013404mg/L | 4      |
| xylene              | EC50     | 48                 | Crustacea                     | >3.4mg/L      | 2      |
| xylene              | EC50     | 72                 | Algae or other aquatic plants | 4.6mg/L       | 2      |
| xylene              | NOEC     | 73                 | Algae or other aquatic plants | 0.44mg/L      | 2      |

## Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus. For example, there is an increase in toxicity as alkylation of the naphthalene structure increases. The order of most toxic to least in a study using grass shrimp (*Palaemonetes pugio*) and brown shrimp (*Penaeus aztecus*) was dimethylnaphthalenes > methylnaphthalenes > naphthalenes.

Studies conclude that the toxicity of an oil appears to be a function of its di-aromatic and tri-aromatic hydrocarbons, which includes three-ring hydrocarbons such as phenanthrene.

Continued...



## MIROBILD AC 3722

The heavier (4-, 5-, and 6-ring) PAHs are more persistent than the lighter (2- and 3-ring) PAHs and tend to have greater carcinogenic and other chronic impact potential. PAHs in general are more frequently associated with chronic risks. These risks include cancer and often are the result of exposures to complex mixtures of chronic-risk aromatics (such as PAHs, alkyl PAHs, benzenes, and alkyl benzenes), rather than exposures to low levels of a single compound.

Anthracene is a phototoxic PAH. UV light greatly increases the toxicity of anthracene to bluegill sunfish. Benchmarks developed in the absence of UV light may be under-protective, and biological resources in strong sunlight are at more risk than those that are not.

For methyl ethyl ketone:

log Kow : 0.26-0.69

log Koc : 0.69

Koc : 34

Half-life (hr) air : 2.3

Half-life (hr) H<sub>2</sub>O surface water : 72-288

Henry's atm m<sup>3</sup>/mol: 1.05E-05

BOD 5 : 1.5-2.24, 46%

COD : 2.2-2.31, 100%

ThOD : 2.44

BCF : 1

#### Environmental fate:

**TERRESTRIAL FATE:** Measured Koc values of 29 and 34 were obtained for methyl ethyl ketone in silt loams. Methyl ethyl ketone is expected to have very high mobility in soil. Volatilisation of methyl ethyl ketone from dry soil surfaces is expected based upon an experimental vapor pressure of 91 mm Hg at 25 deg C. Volatilization from moist soil surfaces is also expected given the measured Henry's Law constant of 4.7x10<sup>-5</sup> atm-cu m/mole. The volatilisation half-life of methyl ethyl ketone from silt and sandy loams was measured as 4.9 days. Methyl ethyl ketone is expected to biodegrade under both aerobic and anaerobic conditions as indicated by numerous screening tests.

**AQUATIC FATE:** Based on Koc values, methyl ethyl ketone is not expected to adsorb to suspended solids and sediment in water. Methyl ethyl ketone is expected to volatilise from water surfaces based on the measured Henry's Law constant. Estimated half-lives for a model river and model lake are 19 and 197, hours respectively. Biodegradation of this compound is expected based upon numerous screening tests. An estimated BCF value of 1 based on an experimental log Kow of 0.29, suggests that bioconcentration in aquatic organisms is low.

**ATMOSPHERIC FATE:** According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere, methyl ethyl ketone, which has an experimental vapor pressure of 91 mm Hg at 25 deg C, will exist solely as a vapor in the ambient atmosphere. Vapour-phase methyl ethyl ketone is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 14 days. Methyl ethyl ketone is also expected to undergo photodecomposition in the atmosphere by natural sunlight.

Photochemical degradation of methyl ethyl ketone by natural sunlight is expected to occur at approximately 1/5 the rate of degradation by photochemically produced hydroxyl radicals.

#### Ecotoxicity:

Fish LC50 (24 h): bluegill sunfish (*Lepomis macrochirus*) 1690-5640 mg/l; guppy (*Lebistes reticulatus*) 5700 mg/l; goldfish (*Carassius auratus*) >5000 mg/l

Fish LC50 (96 h): fathead minnow (*Pimephales promelas*) 3200 mg/l; bluegill sunfish (*Lepomis macrochirus*) 4467 mg/l; mosquito fish (*Gambusia affinis*) 5600 mg/l

Daphnia magna LC50 (48 h): <520-1382 mg/l

Daphnia magna LC50 (24 h): 8890 mg/l

Brine shrimp (*Artemia salina*) LC50 (24 h): 1950 mg/l

For xylenes:

log Koc : 2.05-3.08

Koc : 25.4-204

Half-life (hr) air : 0.24-42

Half-life (hr) H<sub>2</sub>O surface water : 24-672

Half-life (hr) H<sub>2</sub>O ground : 336-8640

Half-life (hr) soil : 52-672

Henry's Pa m<sup>3</sup>/mol: 637-879

Henry's atm m<sup>3</sup>/mol: 7.68E-03

BOD 5 if unstated: 1.4,1%

COD : 2.56,13%

ThOD : 3.125

BCF : 23

log BCF : 1.17-2.41

#### Environmental Fate

**Terrestrial fate:** Measured Koc values of 166 and 182, indicate that 3-xylene is expected to have moderate mobility in soil. Volatilisation of p-xylene is expected to be important from moist soil surfaces given a measured Henry's Law constant of 7.18x10<sup>-3</sup> atm-cu m/mole. The potential for volatilisation of 3-xylene from dry soil surfaces may exist based on a measured vapor pressure of 8.29 mm Hg. p-Xylene may be degraded during its passage through soil. The extent of the degradation is expected to depend on its concentration, residence time in the soil, the nature of the soil, and whether resident microbial populations have been acclimated. p-Xylene, present in soil samples contaminated with jet fuel, was completely degraded aerobically within 5 days. In aquifer studies under anaerobic conditions, p-xylene was degraded, usually within several weeks, with the production of 3-methylbenzylfumaric acid, 3-methylbenzylsuccinic acid, 3-methylbenzoate, and 3-methylbenzaldehyde as metabolites.

**Aquatic fate:** Koc values indicate that p-xylene may adsorb to suspended solids and sediment in water. p-Xylene is expected to volatilise from water surfaces based on the measured Henry's Law constant. Estimated volatilisation half-lives for a model river and model lake are 3 hours and 4 days, respectively. BCF values of 14.8, 23.4, and 6, measured in goldfish, eels, and clams, respectively, indicate that bioconcentration in aquatic organisms is low. p-Xylene in water with added humic substances was 50% degraded following 3 hours irradiation suggesting that indirect photooxidation in the presence of humic acids may play an important role in the abiotic degradation of p-xylene. Although p-xylene is biodegradable and has been observed to degrade in pond water, there are insufficient data to assess the rate of this process in surface waters. p-Xylene has been observed to degrade in anaerobic and aerobic groundwater in several studies; however, it is known to persist for many years in groundwater, at least at sites where the concentration might have been quite high.

#### Atmospheric fate:

Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. In the ambient atmosphere, xylenes are expected to exist solely in the vapour phase. Xylenes are degraded in the atmosphere primarily by reaction with photochemically-produced hydroxyl radicals, with an estimated atmospheric lifetime of about 0.5 to 2 days.

Xylenes' susceptibility to photochemical oxidation in the troposphere is to the extent that they may contribute to photochemical smog formation.

According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere and from its vapour pressure, p-xylene, is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase p-xylene is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 16 hours. A half-life of 1.0 hr in summer and 10 hr in winter was measured for the reaction of p-xylene with photochemically-produced hydroxyl radicals. p-Xylene has a moderately high photochemical reactivity under smog conditions, higher than the other xylene isomers, with loss rates varying from 9-42% per hr. The photooxidation of p-xylene results in the production of carbon monoxide, formaldehyde, glyoxal, methylglyoxal, 3-methylbenzyl nitrate, m-tolualdehyde, 4-nitro-3-xylene, 5-nitro-3-xylene, 2,6-dimethyl-p-benzoquinone, 2,4-dimethylphenol, 6-nitro-2,4-dimethylphenol, 2,6-dimethylphenol, and 4-nitro-2,6-dimethylphenol.

#### Ecotoxicity:

for xylenes

Fish LC50 (96 h) *Pimephales promelas* 13.4 mg/l; *Oncorhynchus mykiss* 8.05 mg/l; *Lepomis macrochirus* 16.1 mg/l (all flow through values); *Pimephales promelas* 26.7 (static)

Daphnia EC50 948 h): 3.83 mg/l

Photobacterium phosphoreum EC50 (24 h): 0.0084 mg/l

Gammarus lacustris LC50 (48 h): 0.6 mg/l

For ketones:

Ketones, unless they are alpha, beta--unsaturated ketones, can be considered as narcosis or baseline toxicity compounds

Hydrolysis may also involve the addition of water to ketones to yield ketals under mild acid conditions. However, this addition of water is thermodynamically favorable only for low molecular weight ketones. This addition is an equilibrium reaction that is reversible upon a change of water concentration and the reaction ultimately leads to no permanent change in the structure of the ketone substrate. The higher molecular weight ketones do not form stable ketals. Therefore, the ketones are stable to water under ambient environmental conditions.

Another possible reaction of ketones in water involves the enolic hydrogen on the carbons bonded to the carbonyl function. Under conditions of high pH (pH greater than 10), the enolic proton is abstracted by base (OH<sup>-</sup>) forming a carbanion intermediate that may react with other organic substrates (e.g., ketones, esters, aldehydes) containing a center for nucleophilic attack. The reactions, commonly recognized as condensation reactions, produce higher molecular weight products. Under ambient conditions of temperature, pH, and low concentration, these condensation reactions are unfavorable.

Based on its reactions in air, it seems likely that ketones undergo photolysis in water. It is probable that ketones will be biodegraded to an appreciable degree by micro-organisms in soil and water.

They are unlikely to bioconcentrate or biomagnify.

For n-butyl acetate:

Half-life (hr) air : 144

Half-life (hr) H<sub>2</sub>O surface water : 178-27156

Henry's atm m<sup>3</sup>/mol: 3.20E-04

BOD 5 if unstated: 0.15-1.02,7%

COD : 78%

ThOD : 2.207

BCF : 4-14

#### Environmental Fate:

**TERRESTRIAL FATE:** An estimated K<sub>oc</sub> value of 200 determined from a measured log K<sub>ow</sub> of 1.78 indicates that n-butyl acetate is expected to have moderate mobility in soil. Volatilisation of n-butyl acetate is expected from moist soil surfaces given its Henry's Law constant of 2.8x10<sup>-4</sup> atm-cu m/mole. Volatilisation from dry soil surfaces is expected based on a measured vapor pressure of 11.5 mm Hg. Using a standard BOD dilution technique and a sewage inoculum, theoretical BODs of 56 % to 86 % were observed during 5-20 day incubation periods, which suggests that n-butyl acetate may biodegrade in soil.

**AQUATIC FATE:** An estimated K<sub>oc</sub> value indicates that n-butyl acetate is not expected to adsorb to suspended solids and sediment in water. Butyl acetate is expected to volatilise from water surfaces based on a Henry's Law constant of 2.8x10<sup>-4</sup> atm-cu m/mole. Estimated half-lives for a model river and model lake are 7 and 127, hours respectively. An estimated BCF value of 10 based on the log K<sub>ow</sub>, suggests that bioconcentration in aquatic organisms is low. Using a filtered sewage seed, 5-day and 20-day theoretical BODs of 58 % and 83 % were measured in freshwater dilution tests; 5-day and 20-day theoretical BODs of 40 % and 61 % were measured in salt water. A 5-day theoretical BOD of 56.8 % and 51.8 % were measured for n-butyl acetate in distilled water and seawater, respectively. Hydrolysis may be an important environmental fate for this compound based upon experimentally determined hydrolysis half-lives of 114 and 11 days at pH 8 and 9 respectively.

**ATMOSPHERIC FATE:** According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere, n-butyl acetate, which has a vapour pressure of 11.5 mm Hg at 25 deg C, is expected to exist solely as a vapor in the ambient atmosphere. Vapour-phase n-butyl acetate is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 4 days

#### Environmental fate:

Fish LC50 (96 h, 23 C): island silverside (*Menidia beryllina*) 185 ppm (static bioassay in synthetic seawater, mild aeration applied after 24 h); bluegill sunfish (*Lepomis macrochirus*) 100 ppm (static bioassay in fresh water, mild aeration applied after 24 h)

Fish EC50 (96 h): fathead minnow (*Pimephales promelas*) 18 mg/l (affected fish lost equilibrium prior to death)

Daphnia LC50 (48 h): 44 ppm

Algal LC50 (96 h): *Scenedesmus* 320 ppm

**DO NOT discharge into sewer or waterways.**

### Persistence and degradability

| Ingredient          | Persistence: Water/Soil     | Persistence: Air             |
|---------------------|-----------------------------|------------------------------|
| n-butanol           | LOW (Half-life = 54 days)   | LOW (Half-life = 3.65 days)  |
| methyl ethyl ketone | LOW (Half-life = 14 days)   | LOW (Half-life = 26.75 days) |
| ethyl acetate       | LOW (Half-life = 14 days)   | LOW (Half-life = 14.71 days) |
| n-butyl acetate     | LOW                         | LOW                          |
| titanium dioxide    | HIGH                        | HIGH                         |
| xylene              | HIGH (Half-life = 360 days) | LOW (Half-life = 1.83 days)  |

### Bioaccumulative potential

| Ingredient          | Bioaccumulation     |
|---------------------|---------------------|
| n-butanol           | LOW (BCF = 0.64)    |
| methyl ethyl ketone | LOW (LogKOW = 0.29) |
| ethyl acetate       | HIGH (BCF = 3300)   |
| n-butyl acetate     | LOW (BCF = 14)      |
| titanium dioxide    | LOW (BCF = 10)      |
| xylene              | MEDIUM (BCF = 740)  |

### Mobility in soil

| Ingredient          | Mobility             |
|---------------------|----------------------|
| n-butanol           | MEDIUM (KOC = 2.443) |
| methyl ethyl ketone | MEDIUM (KOC = 3.827) |
| ethyl acetate       | LOW (KOC = 6.131)    |
| n-butyl acetate     | LOW (KOC = 20.86)    |
| titanium dioxide    | LOW (KOC = 23.74)    |

## SECTION 13 DISPOSAL CONSIDERATIONS

### Waste treatment methods

|                              |  |
|------------------------------|--|
| Product / Packaging disposal | <ul style="list-style-type: none"> <li>Containers may still present a chemical hazard/ danger when empty.</li> <li>Return to supplier for reuse/ recycling if possible.</li> </ul>   |
|                              | <p>Otherwise:</p> <ul style="list-style-type: none"> <li>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>Reduction</li> <li>Reuse</li> <li>Recycling</li> </ul> |

## MIROBILD AC 3722

## ► Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

► **DO NOT allow wash water from cleaning or process equipment to enter drains.**

- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

## SECTION 14 TRANSPORT INFORMATION

## Labels Required

|                  |   |
|------------------|---|
|                  |  |
| Marine Pollutant | NO  |
| HAZCHEM          | •3YE  |

## Land transport (UN)

|                              |  |
|------------------------------|--|
| UN number                    | 1263   |
| Packing group                | II   |
| UN proper shipping name      | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Environmental hazard         | Not Applicable   |
| Transport hazard class(es)   | Class : 3<br>Subrisk : Not Applicable  |
| Special precautions for user | Special provisions : 163; 367<br>Limited quantity : 5 L  |

## Air transport (ICAO-IATA / DGR)

|                              |   |
|------------------------------|---|
| UN number                    | 1263  |
| Packing group                | II  |
| UN proper shipping name      | Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds)   |
| Environmental hazard         | Not Applicable  |
| Transport hazard class(es)   | ICAO/IATA Class : 3<br>ICAO / IATA Subrisk : Not Applicable<br>ERG Code : 3L  |
| Special precautions for user | Special provisions : A3 A72 A192<br>Cargo Only Packing Instructions : 364<br>Cargo Only Maximum Qty / Pack : 60 L<br>Passenger and Cargo Packing Instructions : 353<br>Passenger and Cargo Maximum Qty / Pack : 5 L<br>Passenger and Cargo Limited Quantity Packing Instructions : Y341<br>Passenger and Cargo Limited Maximum Qty / Pack : 1 L |

## Sea transport (IMDG-Code / GGVSee)

|                            |  |
|----------------------------|--|
| UN number                  | 1263   |
| Packing group              | II   |
| UN proper shipping name    | PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Environmental hazard       | Not Applicable   |
| Transport hazard class(es) | IMDG Class : 3<br>IMDG Subrisk : Not Applicable  |

## MIROBILD AC 3722

## Special precautions for user

|                    |          |
|--------------------|----------|
| EMS Number         | F-E, S-E |
| Special provisions | 163 367  |
| Limited Quantities | 5 L      |

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## SECTION 15 REGULATORY INFORMATION

## Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

| HSR Number | Group Standard  |
|------------|---|
| HSR002596  | Laboratory Chemicals and Reagent Kits Group Standard 2006                           |
| HSR002528  | Cleaning Products (Flammable) Group Standard 2006                                   |
| HSR002583  | Fuel Additives (Flammable) Group Standard 2006                                      |
| HSR002662  | Surface Coatings and Colourants (Flammable) Group Standard 2006                     |
| HSR002611  | Metal Industry Products (Flammable) Group Standard 2006                             |
| HSR002621  | N.O.S. (Flammable) Group Standard 2006  |
| HSR002641  | Polymers (Flammable) Group Standard 2006  |
| HSR002637  | Photographic Chemicals (Flammable) Group Standard 2006                              |
| HSR002495  | Additives, Process Chemicals and Raw Materials (Flammable) Group Standard 2006      |
| HSR002576  | Food Additives and Fragrance Materials (Flammable) Group Standard 2006              |
| HSR002563  | Embalming Products (Flammable) Group Standard 2006                                  |
| HSR002556  | Dental Products (Flammable) Group Standard 2006                                     |
| HSR100425  | Pharmaceutical Active Ingredients Group Standard 2010                               |
| HSR002599  | Leather and Textile Products (Flammable) Group Standard 2006                        |
| HSR002603  | Lubricants (Flammable) Group Standard 2006  |
| HSR002650  | Solvents (Flammable) Group Standard 2006  |
| HSR002552  | Cosmetic Products Group Standard 2006   |
| HSR002548  | Corrosion Inhibitors (Flammable) Group Standard 2006                                |
| HSR100757  | Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2012                |
| HSR100758  | Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2012 |
| HSR100759  | Veterinary Medicines (Non-dispersive Open System Application) Group Standard 2012   |
| HSR100628  | Straight-chained Lepidopteran Sex Pheromone Group Standard 2012                     |

## TALC(14807-96-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

## N-BUTANOL(71-36-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals  
New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

## NITROCELLULOSE(9004-70-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft  
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)  
New Zealand Workplace Exposure Standards (WES)

## METHYL ETHYL KETONE(78-93-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals  
New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

## ETHYL ACETATE(141-78-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals  
New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

## N-BUTYL ACETATE(123-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals  
New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Continued...

TITANIUM DIOXIDE(13463-67-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

|   |  |
|---|--|
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs | New Zealand Workplace Exposure Standards (WES) |
| New Zealand Inventory of Chemicals (NZIoC)  |  |

N-TALLOW(ALKYL)-1,3-PROPANEDIAMINE DIOLEATE(61791-53-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

|  |
|--|
| New Zealand Inventory of Chemicals (NZIoC) |
|--|

XYLENE(1330-20-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

|   |  |
|---|--|
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs | New Zealand Inventory of Chemicals (NZIoC)     |
| New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals   | New Zealand Workplace Exposure Standards (WES) |

ECHA SUMMARY

| Ingredient | CAS number | Index No      | ECHA Dossier  |
|------------|------------|---------------|---------------|
| talc       | 14807-96-6 | Not Available | Not Available |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s)   | Pictograms Signal Word Code(s) | Hazard Statement Code(s)     |
|-------------------------------|---|--------------------------------|------------------------------|
| 1                             | Not Classified  | Wng, GHS08, Dgr                | H319, H332, H372, H335, H350 |
| 2                             | Not Classified, Eye Irrit. 2, Acute Tox. 4, STOT RE 1, STOT SE 3, Carc. 1A, Aquatic Chronic 4 | Wng, GHS08, Dgr                | H319, H332, H372, H335, H350 |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

| Ingredient | CAS number | Index No     | ECHA Dossier          |
|------------|------------|--------------|-----------------------|
| n-butanol  | 71-36-3    | 603-004-00-6 | 01-2119484630-38-XXXX |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s)  | Pictograms Signal Word Code(s) | Hazard Statement Code(s)                                   |
|-------------------------------|--|--------------------------------|--|
| 1                             | Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3   | GHS07, GHS02, GHS05, Dgr       | H226, H302, H315, H318, H335, H336                         |
| 2                             | Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, Not Classified, Acute Tox. 2, Eye Irrit. 2, Asp. Tox. 1, STOT RE 1 | GHS02, GHS05, Dgr, GHS08       | H302, H315, H318, H335, H336, H370, H332, H225, H304, H372 |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

| Ingredient     | CAS number | Index No     | ECHA Dossier  |
|----------------|------------|--------------|---------------|
| nitrocellulose | 9004-70-0  | 603-037-00-6 | Not Available |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s)  | Pictograms Signal Word Code(s) | Hazard Statement Code(s)           |
|-------------------------------|--|--------------------------------|------------------------------------|
| 1                             | Flam. Sol. 1   | GHS02, Dgr                     | H228                               |
| 2                             | Expl. 1.1, Flam. Sol. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2                     | GHS07, GHS01, Dgr              | H201, H228, H302, H315, H319, H332 |
| 1                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 2                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 1                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 2                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 1                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 2                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 2                             | Flam. Sol. 1, Expl. 1.1, Flam. Liq. 2, Aquatic Chronic 4, Flam. Sol. 2, Not Classified | Dgr, GHS01, Wng                | H228, H201, H225                   |
| 1                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 2                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 1                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 2                             | Expl. 1.1  | GHS01, Dgr                     | H201                               |
| 1                             | Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1          | GHS07, GHS02, GHS08, Wng       | H226, H312, H315, H319, H335, H373 |
| 2                             | Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1          | GHS02, GHS08, Wng              | H226, H312, H315, H319, H335, H373 |
| 1                             | Expl. 1.1, Flam. Sol. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2                     | GHS07, GHS01, GHS02, Dgr       | H201, H228, H302, H315, H319, H332 |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

| Ingredient          | CAS number | Index No     | ECHA Dossier                                 |
|---------------------|------------|--------------|--|
| methyl ethyl ketone | 78-93-3    | 606-002-00-3 | 01-2119457290-43-XXXX, 01-2119943742-35-XXXX |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s) | Pictograms Signal Word Code(s) | Hazard Statement Code(s) |
|-------------------------------|-----------------------------------|--------------------------------|--------------------------|
|-------------------------------|-----------------------------------|--------------------------------|--------------------------|

## MIROBILD AC 3722

|   |   |                        |  |
|---|---|------------------------|--|
| 1 | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3   | GHS07, GHS02, Dgr      | H225, H319, H336   |
| 2 | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Not Classified, Eye Irrit. 2A | Dgr, Wng, GHS01, GHS08 | H225, H319, H336, H371, H335, H312, H341, H302, H361, H314 |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

| Ingredient    | CAS number | Index No     | ECHA Dossier          |
|---------------|------------|--------------|-----------------------|
| ethyl acetate | 141-78-6   | 607-022-00-5 | 01-2119475103-46-XXXX |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s)   | Pictograms Signal Word Code(s) | Hazard Statement Code(s) |
|-------------------------------|---|--------------------------------|--------------------------|
| 1                             | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3   | GHS07, GHS02, Dgr              | H225, H319, H336         |
| 2                             | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 1, Not Classified, Acute Tox. 4, Asp. Tox. 1, Skin Sens. 1, Aquatic Chronic 3, Eye Irrit. 2A, Flam. Liq. 3 | GHS07, Dgr, GHS01, Wng         | H225, H319, H336, H335   |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

| Ingredient      | CAS number | Index No     | ECHA Dossier          |
|-----------------|------------|--------------|-----------------------|
| n-butyl acetate | 123-86-4   | 607-025-00-1 | 01-2119485493-29-XXXX |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s)  | Pictograms Signal Word Code(s) | Hazard Statement Code(s)                 |
|-------------------------------|--|--------------------------------|--|
| 1                             | Flam. Liq. 3, STOT SE 3  | GHS07, GHS02, Wng              | H226, H336                               |
| 2                             | Flam. Liq. 3, STOT SE 3, Aquatic Chronic 1, Flam. Liq. 2, Skin Irrit. 2, Eye Irrit. 2, Acute Tox. 2, Not Classified, Acute Tox. 4, Aquatic Chronic 2 | Wng, GHS01, Dgr, GHS06, GHS08  | H336, H319, H225, H315, H330, H335, H317 |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

| Ingredient       | CAS number | Index No      | ECHA Dossier                                 |
|------------------|------------|---------------|--|
| titanium dioxide | 13463-67-7 | Not Available | 01-2119954396-27-XXXX, 01-2119489379-17-XXXX |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s)   | Pictograms Signal Word Code(s) | Hazard Statement Code(s)                                   |
|-------------------------------|---|--------------------------------|--|
| 1                             | Not Classified  | GHS08, Dgr, Wng                | H302, H351, H315, H319, H332, H335, H372, H350, H318, H312 |
| 2                             | Not Classified, Acute Tox. 4, Carc. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, STOT SE 2, Carc. 1B, Aquatic Chronic 4, STOT RE 2 | GHS08, Dgr, Wng                | H302, H351, H315, H319, H332, H335, H372, H350, H318, H312 |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

| Ingredient                                  | CAS number | Index No      | ECHA Dossier  |
|---|------------|---------------|---------------|
| N-tallow(alkyl)-1,3-propanediamine dioleate | 61791-53-5 | Not Available | Not Available |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s)  | Pictograms Signal Word Code(s) | Hazard Statement Code(s) |
|-------------------------------|--|--------------------------------|--------------------------|
| 1                             | Acute Tox. 4, Skin Corr. 1C, Aquatic Acute 1, Eye Dam. 1   | GHS07, GHS09, GHS05, Dgr       | H302, H314, H318         |
| 2                             | Acute Tox. 4, Skin Corr. 1C, Aquatic Acute 1, Eye Dam. 1, Skin Irrit. 2, Skin Corr. 1B, Eye Irrit. 2, Aquatic Chronic 3, Not Classified, Aquatic Chronic 1 | GHS09, GHS05, Dgr, Wng         | H302, H314, H318         |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

| Ingredient | CAS number | Index No     | ECHA Dossier          |
|------------|------------|--------------|-----------------------|
| xylene     | 1330-20-7  | 601-022-00-9 | 01-2119488216-32-XXXX |

| Harmonisation (C&L Inventory) | Hazard Class and Category Code(s)   | Pictograms Signal Word Code(s) | Hazard Statement Code(s)   |
|-------------------------------|---|--------------------------------|--|
| 1                             | Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2   | GHS07, GHS02, Wng              | H226, H312, H315, H332   |
| 2                             | Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Not Classified, Asp. Tox. 1, Eye Irrit. 2, STOT SE 3, STOT RE 2, Aquatic Chronic 3, Acute Tox. 3, Aquatic Chronic 2, Repr. 1B, STOT SE 1, STOT RE 1, Flam. Liq. 2, Repr. 2 | Wng, GHS08, Dgr, GHS01, GHS09  | H312, H315, H332, H304, H335, H336, H360, H370, H372, H318, H225 |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

## Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

| Hazard Class | Quantity beyond which controls apply for closed containers                          | Quantity beyond which controls apply when use occurring in open containers |
|--------------|---|--|
| 3.1B         | 100 L in containers greater than 5 L<br>250 L in containers up to and including 5 L | 50 L<br>50 L   |

## Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

| Class of substance | Quantities |
|--------------------|------------|
|--------------------|------------|

Continued...

## MIROBILD AC 3722

|      |  |
|------|--|
| 3.1B | 250 L (when in containers greater than 5 L)        |
|      | 500 L (when in containers up to and including 5 L) |

Refer Group Standards for further information

### Tracking Requirements

Not Applicable

| National Inventory            | Status  |
|-------------------------------|---|
| Australia - AICS              | Y   |
| Canada - DSL                  | Y   |
| Canada - NDSL                 | N (talc; n-butanol; nitrocellulose; xylene; ethyl acetate; n-butyl acetate; methyl ethyl ketone)  |
| China - IECSC                 | Y   |
| Europe - EINEC / ELINCS / NLP | N (nitrocellulose)  |
| Japan - ENCS                  | N (N-tallow(alkyl)-1,3-propanediamine dioleate)   |
| Korea - KECI                  | Y   |
| New Zealand - NZIoC           | Y   |
| Philippines - PICCS           | Y   |
| USA - TSCA                    | Y   |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets) |

## SECTION 16 OTHER INFORMATION

### Other information

#### Ingredients with multiple cas numbers

| Name  | CAS No  |
|---|---|
| titanium dioxide                            | 100292-32-8, 101239-53-6, 116788-85-3, 12000-59-8, 12188-41-9, 12701-76-7, 12767-65-6, 12789-63-8, 1309-63-3, 1317-70-0, 1317-80-2, 1344-29-2, 13463-67-7, 185323-71-1, 185828-91-5, 188357-76-8, 188357-79-1, 195740-11-5, 221548-98-7, 224963-00-2, 246178-32-5, 252962-41-7, 37230-92-5, 37230-94-7, 37230-95-8, 37230-96-9, 39320-58-6, 39360-64-0, 39379-02-7, 416845-43-7, 494848-07-6, 494848-23-6, 494851-77-3, 494851-98-8, 55068-84-3, 55068-85-4, 552316-51-5, 62338-64-1, 767341-00-4, 97929-50-5, 98084-96-9 |
| N-tallow(alkyl)-1,3-propanediamine dioleate | 61790-55-4, 61791-53-5  |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net](http://www.chemwatch.net)

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC — TWA: Permissible Concentration-Time Weighted Average  
 PC — STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit,  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL: No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.